





TAKE CONTROL OF YOUR JOB OPERATIONS

- Touch Panel provides ease of use and reduces operational steps
- Customizable Home screen
- Improved screen visibility for Touch Panel with the use of backlight
- Up to 13 languages* supported

*Supports Malay, Thai, Vietnamese & more



COPY ID CARDS EFFORTLESSLY

- One-touch shortcut key makes copying of ID cards onto a single printout simple and efficient.
- Shortcut setup for ID card copy is not required

ENJOY MORE VALUE WITH imageRUNNER 2206N/2006N

((·)) WIRELESS LAN

Built-in with Wi-Fi capability, the imageRUNNER 2206N/2006N can connect wirelessly to a network via an access point. All other connected electronic devices on the same network will be able to print wirelessly, thereby providing greater convenience to users.





SECURE PRINTING

Protect confidential information from your documents by securing your print job with a configurable PIN.

Documents are held in the printer and released only when a PIN is entered. With the additional layer of verification, this eliminates security risks when printouts are left unattended. It also indirectly reduces paper wastage in the event of a misprint.



SEND LITE

- Scan to Email: Scan your original documents through the platen or automatic document feeder (ADF) and send the scanned document as an attachment to multiple email addresses.
- Scan to SMB: Scan your original documents through the platen or automatic document feeder (ADF) and store your files in the network folder via SMB protocol.
- Au-Send: Send function is available only to authenticated users, deterring various types of potential data leakages.



MOBILE PRINTING

- Supports businesses with mobile printing for a variety of file formats including image files, PDF, Microsoft Office files and web pages.
- Canon PRINT Business: Free download from App Store (iOS) and Google Play (Android)

SERIES LINE-UP

Model	Copy Speed	Network Print	Scan	Send Lite	WiFi	Dept ID	Platen Cover	DADF	Duplex	Max. Paper Cassette
iR2206N	22 pages/min	~	Push / Pull	Send to email/ SMB	~	~	Opt	Opt	Opt	2 x 250 sheets 80g/m² (gsm)
iR2006N	20 pages/min	~	Push / Pull	Send to email/ SMB	~	~	Opt	Opt	Opt	2 x 250 sheets 80g/m² (gsm)
iR2206	22 pages/min	×	Push / Pull	×	×	×	~	×	×	1 x 250 sheets 80g/m² (gsm)

SPECIFICATIONS





GENERAL SPECIFICATIONS		iR2206	iR2006N	iR2206N				
Туре		A3 Monochrome Multifunctional Device (Reader/Printer Desktop)						
Copy/Print Speed	A4	22 pages/min	20 pages/min	22 pages/min				
	A3	11 pages/min	10 pages/min	11 pages/min				
Warm-Up Time (Time from device power on, until cop	y ready)		13s or less					
Recovery from sleep mode First Copy Time (A4)		4.3s 7.4s						
Memory		7.4s 256 MB 512 MB						
Dimensions (W x D x H)		622.0 x 589.0 x 499.0 mm						
Weight		Approximately 28.7Kg Approximately 35.5 kg (with ADF)						
Installation Space (W × D)		920.0 x 589.0 mm (when multi purpose tray is extended)						
Power Supply		220 to 240 V AC, 50/60 Hz, 2.4 A	220 to 240 V AC, 50/60 Hz, 2.4 A 220 to 240 V AC, 50/60 Hz, 2.7 A					
Max Power Consumption	Maximum Power Consumption:	1.5 kWh						
	When the machine is in the Sleep mode:		2 W					
Toner Yield (A4, 6% coverage)		Approx 10 200 sheets (A4, 6% coverage) Approx 66 000 sheets Approx 63 700 sheets Approx 66 000 sheets						
Drum Yield		Approx 66 000 sheets	Approx 63 700 sneets	Approx 66 000 sheets				
PRINT SPECIFICATIONS								
Print Resolution			600 x 600dpi					
Page Description Language(s)		UFRII LT (Standard)	UFRILLT (Standard), PCL6 (Optional)					
Print OS Compatibility			Windows 10/ 8.1/7, Windows Server 2008/ 2008 R2/ 2012/ 2012 R2/ 2016, Mac OS X 10.9.5 or later					
nterface	Network Network	N/A Ethernet 100Base-Tx/10Base-T (IEEE 802.3 compliant), WLAN IEEE 802.11b/g/n						
Natural Protocol	Others (Local Print/Scan)	USB2.0 x 1						
Network Protocol		N/A	N/A TCP/ IP (IPv4/IPv6), USB ;Frame type: Ethernet II, Print applications: LPD/ R / IPPS/ WSD/ Mopria/ Google Cloud Print/ AirPrint/ Windows10 Mobile					
CODY SPECIFICATIONS								
COPY SPECIFICATIONS			(00 (00))					
Copy Resolution		600 x 600dpi						
Multiple Copies/Prints			Up to 999 copies					
Magnification			25% - 400% (1% increment)					
SEND SPECIFICATIONS				1.6.11				
Destination		N/A	Scan to Email (SMTP),	network folders (SMB)				
Scan Speed (Platen, A4, 600dpi)			BW: 1.71 secs, CL: 3.42 secs					
Scan Speed (Simplex, A4, 300dpi)		N/A	BW: 13 sheets/ minute, CL: 6 sheets / minute					
Address Book		N/A	LDAP (5)/Local(104) / One-touch(4)					
END Resolution		N/A	BW/CL 300 x 300dpi					
SEND File Format		N/A	PDF/ Compact F	PDF/ JPEG/ TIFF				
SCAN SPECIFICATIONS								
Destination		MF Sca	an Utility, application compatible with TWA	IN/WIA				
Supported Protocol		TCP/ IP, USB						
Scan Speed (Simplex, A4, 300dpi)		B	BW: 23 sheets/ minute, CL: 12 sheets / minute					
Scan Resolution		BW: 600 x 600dpi, CL: 300 x 600dpi TIFF/ JPEG/ PNG/ PDF (Compact, Searchable) / PDF (Divided into Single-Page Files)						
Scan File Format								
Scan OS Compatibility		Windows 10/ 8.1/ 7, Window	ws Server2008/ 2008 R2/ 2012/ 2012 R2/ 2	016, Mac OS X 10.9.5 or later				
SECURITY								
Authentication		N/A		gement (Max: 100 IDs)				
Network		N/A	Standard: IP/Mac Address Filtering, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6,					
		171		Authentication before SMTP				
Document		N/A	Secur	re Print				
PAPER HANDLING								
Paper Sizes	Casette 1	A3, B4, A4R, A4, B5, B5R, A5R, India-LGL, FOOLSCAP						
	Cassette 2	-						
	Multi Purpose Tray	A3, B4, A4R, A4, B5, B5R, A		SCAP, Envelope (COM 10, Monarch, ISO-C5, DL)				
Paper Input Capacity (Standard)	Cassette 1		250 sheets 80g/m² (gsm)					
	Multi Purpose Tray		80 sheets 80g/m² (gsm)					
Paper Input Capacity (Optional)	Cassette 2*	N/A	250 sheet	ts 80g/m² (gsm)				
Paper Specification	Cassette	Weight: 64 - 90g/m² (gsm), Type: Plain 64 to 90g/	Weight: 64 - 90g/m² (gsm), Type: Plain 64 to 90g/m² (gsm), Recycled 65 to 80g/m² (gsm), Colour 64 to 80g/m² (gsm), Pre-punched 75 to 80g/m² (gsm), Colour 64 to 80g/m² (gsm), Pre-punched 75 to 80g/m² (gsm), Pre-punched 85 t					
	Multi Purpose Tray	Weight: 60 - 128g/m² (gsm); Type: Plain 64 to 90g/m² (gsm), Heavy 1 91 to 105g/m² (gsm), Heavy 2 106 to 128g/m² (gsm), Recyded 65 to 80g/m² (gsm) Colour 64 to 80g/m² (gsm); Pre-punched 75 to 80g/m² (gsm), Bond 75 to 90g/m² (gsm), Transparency, Label, Envelope						
OPTIONAL ACCESSORIES DUPLEX AUTOMATIC DOCUMENT FEEDER - AY1*								
		N/A	Automatic Do	cument Feeder				
Size of Originals		N/A		5, A5R, FOOLSCAP, India LGL				
aper Weight		N/A		nuously: 52 to 105g/m²				
				original: 37 to 128g/m²				
Max. Number of Originals		N/A		A4, 80g/m² (gsm)				
Scanning Speed (Simplex)	Copying (A4 in BW at 600dpi)	N/A	20 images/min	22 images/min				
2:	Scanning (A4 in BW 300dpi)	N/A		ages/min				
Dimensions (W x D x H)		N/A		0.5 x 126.0 mm				
Weight	IDDLIFC	N/A	Approxim	ately 7.0 kg				
OTHER OPTIONAL ACCESSORIES AND SI Ouplex Unit-C1*, Platen Cover Type X*, Cassette Feedi Available for iR2206N/2006N only.		2, Cassette Heater Unit-40, NPG-59 Drum Unit, NP	G-59 Black Toner					

To arrange for a demonstration, simply contact:

CANON INDIA PVT. LTD.

7th Floor, Tower B, Building #5, DLF Epitome Building, DLF Phase III, Gurugram-122002 Ph.: 0124-4160000 | Fax: 0124-4160011 | Web: in.canon

Disclaimer: This document is for information purpose only and the contents are subject to change without notice. Product options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations with respect to this document. Canon and Business Can Be Simple are trademarks of Canon Inc, and/or its affiliates. Other names may be the trademarks for their respective owners.

DEALER'S STAMP